



Main

Range of product	Acti 9
Product name	Acti 9 Smartlink
Product or component type	Smart communication module
Device short name	Smartlink Modbus
Application type	Load control Breaker status monitoring Basic energy metering E
Number max of connected devices	Up to 11 wired devices
Group of channels	1 group of 11 digital channels
Maximum supply current	1.5 A
[Us] rated supply voltage	24 V DC +/- 20 %
Connectivity to devices	Digital input and output Pulse output meter
Communication service	Modbus slave for RS485
Web server	BMS controller compatible
Web services	Web page

Complementary

Application specific I/O	Pulse totalising counter Pulse converter
Protection type	Short-circuit protection for analog input Against reverse polarity for auxiliary supply Against reverse polarity for input Overvoltage at 33 V DC for digital output
Immunity to microbreaks	10 ms
Reset	Factory reset on front face
Input/Output type	2 inputs + 1 output per digital channel
Input type	Current sink for digital input, 24 V DC +/- 20 % at 2.5 mA
Maximum permanent current	5 mA for digital input
Electronic filtering time	2 ms for digital input from state 0 to state 1
Output type	Logic current source: 24 V - DC - 100 mA
Maximum voltage drop	<1 V at state 1 digital output

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Inrush current	0.5 A for digital output 3 A for power supply
Local signalling	Communication: 1 LED (yellow) Status: 1 LED (green, orange and red)
Type of setting	Modbus address 01...99 for address encoders Reset for address encoders Reset for plug in, plug out the auxiliary supply
Mounting position	Horizontal and vertical on DIN rail
Colour	White (RAL 9003)
Location of connection	Front
Connections - terminals	Spring-loaded terminal Ti24 qty: 11 for digital input/output, ordered separately Plug-in connector qty: 1 for supply circuit Plug-in connector qty: 1 for communication bus
Clamping connection capacity	2 x 0.25 mm ² for twisted shielded pairs cable, flexible with cable end for communication bus 2 x 0.25 mm ² for twisted shielded pairs cable, flexible without cable end for communication bus 2 x 0.25 mm ² for twisted shielded pairs cable, rigid with cable end for communication bus 2 x 0.25 mm ² for twisted shielded pairs cable, rigid without cable end for communication bus 1 x 0.5...1 x 1.5 mm ² , flexible with cable end for control 1 x 0.5...1 x 1.5 mm ² , flexible without cable end for control 1 x 0.5...1 x 1.5 mm ² , rigid with cable end for control 1 x 0.5...1 x 1.5 mm ² , rigid without cable end for control 2 x 0.2...2 x 1.5 mm ² , flexible with cable end for supply circuit 2 x 0.2...2 x 1.5 mm ² , flexible without cable end for supply circuit 2 x 0.2...2 x 1.5 mm ² , rigid with cable end for supply circuit 2 x 0.2...2 x 1.5 mm ² , rigid without cable end for supply circuit
Wire stripping length	Control: 10 mm Supply circuit: 7 mm Communication bus: 7 mm
Communication network type	RS485 Modbus RTU slave SUB-D 9 9.6...19.2 kbauds
9 mm pitches	0 useful
Height	22.5 mm
Width	359 mm
Depth	42 mm
Net weight	195 g
Provided equipment	Set of 1 bus connector Set of 1 power supply connector Set of 2 locking clips
Range compatibility	iTL auxiliary Linergy FM iOF+SD 24 iACT24 iATL24 pulse output meter RCA iC60 Acti 9 iCT auxiliary Acti 9 iC60 Acti 9 iID Acti 9 iSW-NA Acti 9 iDPN Vig Acti 9 C40 Multi 9 C60 Acti 9 DT40 Acti 9 DT60 Acti 9 I-NA Acti 9 ITG40 Acti 9 iDPN Acti 9 Reflex iC60 Ti24 connector
Commissioning interface	ECOREACH Web page
Market segment	Residential Small commercial
Compatibility code	Acti 9 Smartlink

Environment

IP degree of protection	IP20
-------------------------	------

Pollution degree	3
Electromagnetic compatibility	Resistance to electrostatic discharge (air discharge), 8 kV, conforming to IEC 61000-4-2 Resistance to electrostatic discharge (contact discharge), 4 kV, conforming to IEC 61000-4-2 Resistance to radiated electromagnetic fields (80 MHz...3 GHz), 10 V/m, conforming to IEC 61000-4-3 Power supply: resistance to fast transient (5...100 kHz), 2 kV, conforming to IEC 61000-4-4 Input/output: resistance to fast transient, 1 kV, conforming to IEC 61000-4-4 Communication bus: resistance to fast transient, 1 kV, conforming to IEC 61000-4-4 Conducted EMC (0.15...80 MHz), 10 V, conforming to IEC 61000-4-6 Immunity to magnetic fields at network frequency, 30 A/m, conforming to IEC 61000-4-8
Environmental characteristic	Corrosive 3C2 conforming to IEC 60721-3-3 Salt mist 2 conforming to IEC 60068-2-52
Vibration resistance	1 gn, amplitude = 3.5 mm (f = 5...300 Hz)10 cycles conforming to EN/IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Fire resistance	Other parts: 650 °C (30 s) conforming to IEC 60695-2-10 On connection terminals: 960 °C (30 s) conforming to IEC 60695-2-10
Tropicalisation	2
Relative humidity	93 % at 40 °C
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	271 g
Package 1 Height	3.4 cm
Package 1 width	6.4 cm
Package 1 Length	36.4 cm
Unit Type of Package 2	S03
Number of Units in Package 2	32
Package 2 Weight	9.063 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------