

mini Kaedra - for modular device - 1 openings - 4 modules - 2 terminal blocks

Local distributor code:

4024927 13441

EAN Code: 3303430134411

Main

Range	Mureva	
Product name	Mureva Enclosure	
Product or component type	Weatherproof enclosure	
enclosure type	Mini enclosure for modular device	
Mounting plate description	Without mounting plate	

Complementary

Enclosure mounting	Surface	
9 mm pitches	8	
Number of 18 mm modules per row	4	
Total number of 18 mm modules	4	
Number of horizontal rows	1	
Electrical insulation class	Double insulation Class II	
Provided equipment	1 marking kit 2 terminal block 4 holes	
Type of front cover	Transparent	
Power dissipation in W	10 W	
[In] rated current	63 A	
Type of rail	DIN	
Number of pre-cutouts PG ISO	3	
Number of terminal blocks	2 earth / neutral (screw connection) with 4 outgoers	
Distribution block outgoers	4 x 10 mm ² 4 x 16 mm ²	
Locking options description	Optional keylock	
Enclosure material	Self-extinguishing polymer	
Width	123 mm	
Height	200 mm	
Depth	112 mm	
Internal depth	56 mm	
Colour	Door: transparent green Enclosure: light grey (RAL 7035)	

Environment

Standards	IEC 60670-1 IEC 60670-24 EN 50262 IEC 60695-2-1	
Fire resistance	650 °C conforming to IEC 60695-2-1	
IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK09 conforming to EN 50102	
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013	
Overvoltage category	П	
Ambient air temperature for operation	-2560 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	12.000 cm
Package 1 Length	20.000 cm
Package 1 Weight	527.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	9
Package 2 Height	22.500 cm
Package 2 Width	34.500 cm
Package 2 Length	41.000 cm
Package 2 Weight	5.150 kg
Unit Type of Package 3	P12
Number of Units in Package 3	216
Package 3 Height	98.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	135.600 kg

Logistical informations

Country of origin

Contractual warranty

Warranty (in months) 18



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Total lifecycle Carbon footprint	4
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Average percentage of recycled plastic content	25 %
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	5305d5d6-3783-4b3d-abd0-61fa4a6023d7
REACh Regulation	REACh Declaration
Halogen-free status	Halogen free product

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No